



→ ISOLMANT FASCIA PERIMETRALE TECNICA RETICOLATA

Expanded cross-linked closed-cell polyethylene strips designed for easy installation. These strips come with a screen-printed side with the installation instructions.

This product is available in three versions:

- h 12.5 cm (7.5 cm wall + 5 cm floor);
- h 18.5 cm (11 cm wall + 7.5 cm floor);
- h 25 cm (17.5 cm wall + 7.5 cm floor).

**isolmant**FasciaPRM

THICKNESS	Approx. 5 mm
FLANKING PATH NOISE REDUCTION	The non-use of Isolmant Fascia Perimetrale causes an acoustic bridge and a consequent decibel loss
INSTALLATION	<ul style="list-style-type: none"> • After removing the protection film of the adhesive side, Isolmant Fascia Perimetrale can be installed on the floor (or the resilient layer already positioned) and then to the wall • The extra length could be trimmed with "snap-off blade" utility knife after completing flooring installation and finishing
SIZE	12.5 - 18.5 - 25 cm x 50 m strips
PACKAGING	Version h 12.5 cm: 12 rolls equal to 600 m Version h 18.5 cm: 8 rolls equal to 400 m Version h 25 cm: 6 rolls equal to 300 m

→ Conditions of use

In order to ensure floating floor performances also the screed vertical surfaces should be insulated. In addition, as an alternative to turn up and bend the resilient layer along the edges of the floating screed (which is sometimes difficult during installation), it is possible to apply Isolmant Fascia Perimetrale along the room perimeter. Designed for easy installation, this flanking strip ensures an high-level of acoustic performance.

→ Item specifications

Perimeter flanking strip made of expanded closed-cell cross-linked polyethylene with approx. 30 density kg/m³. This product is designed for easy installation. These strips come with a screen-printed side with installation instructions. height cm (12.5 - 18.5 - 25 cm), packaging:rolls of (12 - 8 - 6) 50 m/each. Thickness approx. 5 mm.

WARNING: This technical data sheet is not a valid specification and, if it consist of multiple pages, be sure to read the full document. This instruction are the best of our current experience but are indicative information. Assuming the liability resulting from the use of this product, it is up to the user to establish whether the product is suitable for the intended use.

isolmant by TECNASFALTI