

**→ ISOLMANT FASCIA PERIMETRALE
STACCA/ATTACCA**

15 cm height adhesive strips made of 3 mm Isolmant with reusable adhesive side.

**isolmant FasciaPRM**

THICKNESS	Approx. 3 mm
FLANKING PATH NOISE REDUCTION	The non-use of Isolmant Fascia Perimetrale causes an acoustic bridge and a consequent decibel loss
INSTALLATION	<ul style="list-style-type: none"> • Use this adhesive side to connect the strips to wall, floor or insulating layer • Trim the extra length only after laying and grouting tile flooring and before installing the skirting boards
SIZE	Strips of 15 cm x 100 m
PACKAGING	10 rolls equal to 1000 m

→ Conditions of use

Isolmant Fascia Perimetrale avoids flanking noise and vibration transmission from floating screed to the partition wall. To ensure the proper functioning of the floating floor it is necessary that the whole system resting on the resilient layer can move freely. Flanking strips avoid any rigid contacts between screed and walls, pillars and façades. It can substitute the elastic material used for expansion joints.

→ Item specifications

Adhesive strip for the perimeter acoustic insulation made of expanded closed-cell cross-linked polyethylene with approx. 30 density kg/m³. Height 15 cm. It is provided in boxes of 10 elements of 100 m each. Thickness approx. 3 mm.

WARNING: This technical data sheet is not a valid specification and, if it consist of multiple pages, be sure to read the full document. This instruction are the best of our current experience but are indicative information. Assuming the liability resulting from the use of this product, it is up to the user to establish whether the product is suitable for the intended use.